

imageRUNNER ADVANCE C256/C356 II series

INTELLIGENT, VERSATILE COLOUR A4 MULTIFUNCTIONAL* WITH FLEXIBLE CONNECTIVITY

C356P II is a printer only model



QUICK FACTS

- **Format:** Colour A4
 - **Maximum number of Paper Cassettes:** 4
 - **Paper input Capacity:** 2,300 sheets
 - **Finishing Capabilities:** Collate, Group, Offset, Staple,
 - **ADF Capacity:** 100 sheets
 - **ADF Type:** Platen and DADF
-
- **A4 Colour Print Speed Range:** 25 - 35ppm
 - **Scan Speed:** 50ipm
-
- **Print Languages:** UFR II, PCL6, Adobe PostScript 3
 - **Print Resolution:** 1,200 x 1,200

- Suitable for small workgroups in either a desktop, or floor standing environment
- V² (Vivid & Vibrant) imaging technology ensures documents impress time after time and stand out from the rest
- Class leading Typical Electricity Consumption (TEC) ratings
- Consumes as little as 0.8W in sleep mode
- Qualifies for the latest stringent Blue Angel certification
- CS Toner (consistently stable) provides a top print quality even for high volume print jobs
- Fusing technologies, CS toner, and innovative sleep mode features help lower overall energy consumption.
- Save on transmission costs by utilising the Fax over IP option*
- Optional Cassette Lock to protect your investment
- Options for cost recovery and coin vending integration

UNIFIED FIRMWARE PLATFORM

Common Firmware and features that apply to all imageRUNNER ADVANCE Generation 3 2nd Edition models

SECURITY:

- Prevent unauthorised distribution of sensitive information with our most secure imageRUNNER ADVANCE ever through an array of standard and optional document security features
- Choose from device based or Cloud based authentication without the need for an additional server
- Ability to disable functions by user to prevent unauthorised usage
- Secure Print and Mailbox enhance document confidentiality
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology
- Mitigate the risk associated with the governance of sensitive information and data privacy (PII data) with the Industry-first Data Loss Prevention and auditing of prints, copies, scans and faxes through uniFLOW

PRODUCTIVITY:

- Advanced personalisation enables a unique, personal experience tailored to meet each user's workflow needs.
- Intuitive user interface with a large, responsive colour touchscreen with smart phone-like usability
- Motion sensor technology wakes device from sleep mode.
- Convenient Staple-on-demand functionality.
- Automatically remove blank pages when scanning.
- Scan and convert documents to Searchable PDF, Microsoft® Word, and Microsoft® PowerPoint
- Effortless capturing of paper-based documents with rapid single pass scanning (DADF) and smart media handling capabilities such as multi-sheet feed detection, help speed up the process of digitising documents.
- Secure mobile printing as standard
- Enable guest printing with Direct Connection
- Substitute your PC for your smart device to complete your day-to-day workflows
- Support for industry standards such as Apple Airprint® and Mopria®

Canon

imageRUNNER ADVANCE C256/C356 II series

INTEGRATION:

- Tight integration with uniFLOW Online Express, a Cloud based output management system
- uniFLOW Online Express provides extensive tracking and reporting capabilities from a central web based system.
- Collaborates with business applications and external systems in the cloud
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions such as uniFLOW
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices, check device status and consumables, turn off devices remotely, capture meter readings, as well as manage address books and printer drivers
- Supports industry and network standards i.e. PCL and Adobe PostScript for seamless integration

COST MANAGEMENT:

- Technology designed to reduce total cost of print
- User activity tracking provides visibility of print behaviour
- Apply policies and restrict usage at function level by user*

- Remote diagnostics and assistance, help reduce costs by minimising downtime and time spent by IT resolving issues
- Remote and centralised fleet management simplifies IT management of devices and fleets

QUALITY AND RELIABILITY:

- Designed to achieve maximum uptime with intuitive user maintenance videos and status notifications, to help keep supplies replenished.
- Canon's signature reliability and engine technologies provide high quality output to meet the needs of busy departments.
- Quiet finishing provides less interruptions to workers, keeping employees productive

SUSTAINABILITY:

- Incorporates sustainable design and a focus on minimising environmental impact
- ENERGY STAR® qualified
- Minimise waste with default 2-sided printing, secure printing, and the ability to hold print jobs, preview them and change print settings at the device, achieving the desired results at the first time of printing

Main configuration options



This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the online product configurator. II* indicates that this model has been upgraded to new system software and includes additional security features as standard.

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE C256/C356 II series

| | | | |
|-------------------------------------|---|---------------------------------------|--|
| MAIN UNIT | Colour Laser Multifunctional | Print Resolution | 1200 dpi x 1200 dpi equivalent (1200 dpi mode) |
| Machine type | iR-ADV C256i II*/C356i II*: Print, Copy, Scan, Send, Store and Optional Fax | Page description languages | UFR II, PCL 6, Genuine Adobe PostScript Level 3 (Standard) |
| Core functions | iR-ADV C356P II*: Print | Double Sided Printing | Automatic (Standard) |
| Processor Speed | Canon Dual Custom Processor (Shared) 1.75 Ghz | Direct Print | Direct printing available from USB memory key, Advanced space, Remote UI and Web Browser [†] Supported file types: TIFF, JPEG, PDF, EPS, and XPS. |
| Control Panel | 25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touch panel | Printing from mobile and cloud | A range of software and MEAP-based solutions is available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information |
| Memory Standard | Standard: 3.0GB RAM | Fonts | PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T* (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts** PS fonts: 136 Roman *Requires optional PCL INTERNATIONAL FONT SET-A1 **Requires optional BARCODE PRINTING KIT-D1 |
| Hard Disk drive | Standard: 250GB | Operating System | UFR II: Windows Vista/Server 2008/7/Server 2008 R2/Server 2012/8.1/Server 2012 R2/10/Server 2016, MAC OS X (10.7 or later) PCL: Windows Vista/Server 2008/7/Server 2008 R2/Server 2012/8.1/Server 2012 R2/10/Server 2016 PS: Windows Vista/Server 2008/7/Server 2008 R2/Server 2012/8.1/Server 2012 R2/10/Server 2016, MAC OS X (10.7 or later) PPD: Windows Vista/7/8.1/10, MAC OS X (10.3.9 or later) |
| Interface Connection | NETWORK Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n); Optional: NFC, Bluetooth Low Energy OTHERS Standard: USB 2.0 (Host) x1, USB 3.0 (Host) x1, USB 2.0 (Device) x1; Optional: Serial Interface, Copy Control Interface | | SAP Device Types are available via the SAP Market Place. Please refer to http://software.canon-europe.com/ for availability of print solutions for other operating systems and environments including A5/400, UNIX, Linux [‡] and Citrix. Some of these solutions are chargeable. |
| Paper input (Standard) | 550-sheet cassettes (80gsm) 100-sheet multi-purpose tray (80gsm) | COPY SPECIFICATIONS* | |
| Paper input | 550-sheet cassettes (80 gsm) (CASSETTE MODULE-AE1) 550-sheet cassettes (80gsm) (CASSETTE FEEDING UNIT-AJ1) 3 x 550-sheet cassettes (80gsm) (CASSETTE FEEDING UNIT-AK1) | Copy Speed | iR ADV C256i II*: 25 ppm (A4), 26 ppm (B5), 26 ppm (A5) iR ADV C356i II*: 35 ppm (A4), 26 ppm (B5), 26 ppm (A5) |
| Maximum paper input capacity | 2,300 sheets (80 gsm) | First-Copy-Out Time | iR ADV C256i II*: Approx. 6.9/9.4 seconds or less iR ADV C356i II*/C356P II*: Approx. 5.1/6.9 seconds or less |
| Paper output capacity | Without Finisher: 250 Sheets (A4, 80 gsm) With Finisher: Max.500 sheets (A4, 80 gsm) | Copy resolution | Reading: 600 dpi x 600 dpi Printing: Up to 2.400 dpi equivalent x 600 dpi |
| Finishing capabilities | Collate, Group With External Finisher : Collate, Group, Offset, Staple | Multiple Copies | Up to 999 copies |
| Supported media types | Cassette: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Bond paper, Envelope* *Envelope supported via standard cassette 1 only Multi-purpose tray: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Label, Bond paper, Envelope | Magnification | 25% - 400% (1% Increments) |
| Supported media sizes | Cassette 1: Standard size: A4, B5, A5, Envelopes (No. 10(COM10), Monarch, ISO-C5, DL) Custom size: Min. 98 mm x 190.5 mm up to 216 mm x 355.6 mm Multi-purpose tray: Standard size: A4, B5, A5 Custom Size: Min. 98 mm x 148 mm up to 216 mm x 355.6 mm Envelopes: No.10 (COM10), Monarch, ISO-C5, DL Envelope custom size: 98 mm x 148 mm to 216 mm x 355.6 mm CASSETTE MODULE-AE1: Standard size: A4, B5, A5 Custom size: Min. 98 mm x 190.5 mm up to 216 mm x 355.6 mm CASSETTE FEEDING UNIT-AJ1: Standard size: A4, B5, A5 Custom size: Min. 98 mm x 190.5 mm up to 216 mm x 355.6 mm CASSETTE FEEDING UNIT-AK1: Standard size: A4, B5, A5 Custom size: Min. 98 mm x 190.5 mm up to 216 mm x 355.6 mm | Preset Reductions | 25%, 50%, 71%, 100% |
| Supported media weights | Cassette: 60 to 163 gsm Multi-purpose tray: 60 to 220 gsm Duplex: 60 to 163 gsm | Preset Enlargements | 141%, 200%, 400% |
| Warm-up Time | From Power on: iR ADV C256i II*: 34 seconds or less ² iR ADV C356i II*/C356P II*: 30 seconds or less ² From Sleep Mode: 10 Seconds or Less Quick Start-up Mode: 4 seconds or less ³ | SCAN SPECIFICATIONS* | |
| Dimensions (W x D x H) | iR ADV C256i II*/C356i II*: 511 mm x 651 mm x 639 mm iR ADV C356P II*: 511 mm x 651 mm x 541 mm | Standard type | Single-pass Duplexing Automatic Document Feeder (DADF) |
| Installation Space(W x D) | 511 mm x 651 mm (Basic: Platen cover + Multi-purpose tray extended) 1,407 mm x 908 mm (Fully configured: Platen cover + STAPLE FINISHER-Z1+ Multi-purpose tray extended) 852 mm x 908 mm (Basic: DADF + Multi-purpose tray extended) 1,407 mm x 908 mm (Fully configured: DADF + STAPLE FINISHER-Z1 + Multi-purpose tray extended) | Pull Scan Spec | Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows Vista/7/8.1/10/Server 2008/2008 R2/2012/2012 R2/2016 |
| Weight | iR ADV C256i II*/C356i II*: Approx. 49 Kg including toner iR ADV C356P II*: Approx. 42 Kg including toner | Scan Resolution | 100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi |
| PRINT SPECIFICATIONS | | Acceptable Originals | Platen media size: Sheet, Book, 3-Dimensional Objects Document Feeder media size : A4, B5, A5, A6 Document Feeder media weight : 1-sided scanning: 50 to 128 gsm/64 to 128 gsm (BW/CL) 2-sided scanning: 50 to 128 gsm/64 to 128 gsm (BW/CL) Send functionality available on all models |
| Printing method | Colour Laser Beam Printing | Scan Method | Scan to USB Memory Key: Available on all models Scan to Mobiles or internet-connected devices: A range of solutions is available to provide scanning to mobile devices or internet-connected devices depending on your requirements. Please contact your sales representative for further information Scan to cloud-based services: A range of solutions is available to provide scanning to cloud-based services depending on your requirements. Please contact your sales representative for further information |
| Print Speed | iR ADV C256i II*: 25ppm (A4), 26ppm (B5), 26 ppm (A5) iR ADV C356i II*/C356P II*: 35 ppm (A4), 26 ppm (B5), 26 ppm (A5) | Scan Speed (BW/CL; A4) | TWAIN/WIA Pull scanning available on all models Single-sided Scanning (BW): 50 ipm (300 dpi x 300 dpi) / 50 ipm (300 x 600 dpi) Single-sided Scanning (Colour): 50 ipm (300 dpi x 300 dpi) / 50 ipm (300 x 600 dpi) Double-sided Scanning (BW): 100 ipm (300 dpi x 300 dpi) / 100 ipm (300 x 600 dpi) Double-sided Scanning (Colour): 100 ipm (300 dpi x 300 dpi) / 100 ipm (300 x 600 dpi) |
| | | Paper Capacity | 100 Sheets (80 gsm) |
| | | Double sided scanning | 2-sided to 2-sided (Automatic) |



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE C256/C356 II series

SEND SPECIFICATIONS¹

| | |
|---------------------------------|---|
| Optional / Standard | Standard on all models |
| Destination | E-mail/Internet FAX (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 FAX(Optional), IP Fax(Optional) |
| Address Book/speed dials | LDAP (2,000)/Local (1,600)/Speed dial (200) |
| Send resolution | 100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi |
| Communication protocol | File: FTP, SMB v3.0, WebDAV E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full) |
| File Format | Standard: TIFF, JPEG, PDF(Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b), XPS(Compact, Searchable), Office Open XML (PowerPoint, Word), PDF/XPS(Digital Signature) Optional: PDF(Trace&Smooth, Encrypted) |

FAX SPECIFICATIONS¹

| | |
|---------------------------------|--|
| Optional / Standard | Optional on iR ADV C256i II*/C356i II* |
| Modem Speed | Super G3: 33.6 kbps G3: 14.4 kbps |
| Compression Method | MH, MR, MMR, JBIG |
| Resolution | 400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi |
| Sending/Recording Size | A4, B5*, A5* and A6* *Sent as A4 |
| FAX memory | Up to 30,000 pages |
| Speed dials | Max. 200 |
| Group dials/destinations | Max. 199 dials |
| Sequential broadcast | Max. 256 addresses |
| Memory backup | Yes |

SECURITY SPECIFICATIONS

| | |
|-----------------------|--|
| Authentication | Standard: Universal Login Manager (Device and Function Level Log-in), uniFLOW Online Express Cloud based management software, User Authentication, Department ID, Authentication, Access Management System Optional: Follow me Printing secure print (Requires uniFLOW) |
| Data | Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Common Criteria Certification (DIN ISO 15408) ⁸ Optional: Data Loss Prevention (Requires uniFLOW) |
| Network | Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME |

Document

Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device signature, Secure Watermarks
Optional: User signature, Document Scan locking¹

ENVIRONMENTAL SPECIFICATIONS

Operating Environment

Temperature: 10 to 30 °C (50 to 86 °F)
Humidity: 20 to 80 % RH (no condensation)
220-240 V (±10 %), 50/60 Hz (±2 Hz), 3.9 Amp

Power source

Power consumption

Maximum: Approx. 1.5 kW
Printing: iR-ADV C356P II*: 488.5 wh or less
iR-ADV C256i II*/C356i II*: 575.4 Wh or less
Standby: Approx. 40.3 Wh
Sleep mode: Approx. 0.8 W or Less⁵
Plugin Off: Approx. 0.5W
Typical Electricity Consumption (TEC) rating⁶: 1.3 kWh (iR-ADV C356i II*/C356P II*)
0.7 kWh (iR-ADV C256i II*)

Noise levels

Sound Power Level (LwAd)⁷
iR-ADV C256i II*/C356P II*: Active (BW): 70.2 dB or less, Active (CL): 70.2 dB or less, Standby: 43 dB or less
iR-ADV C356i II*/C356P II*: Active (BW): 71.8 dB or less, Active (CL): 71.8 dB or less, Standby: 53 dB or less
Sound Pressure (LpAm)⁷
Bystander's position:
iR-ADV C356P II*/C356i II*: Active (BW): 52 dB or less, Active (CL): 53 db or less, Standby: 6 dB or less
iR-ADV C256i II*: Active (BW): 49 dB or less, Active (CL): 50 db or less, Standby: 8 dB or less

Standards

ENERGY STAR® Qualified
Ecomark
Blue Angel

CONSUMABLES

Toner Cartridge/s

C-EXV 55 TONER BK/C/M/Y

Toner (Estimated Yield @5% Coverage)

C-EXV 55 TONER BK : 23,000
C-EXV 55 TONER C/M/Y: 18,000

HARDWARE ACCESSORIES

For full information on options available for the iR-ADV C256/C356 II* series, please refer to the specification tables on your local Canon web site.

Footnotes

- II* indicates that this model has been upgraded to new system software and includes additional security features as standard.
- ¹ Not applicable to the C356P II* as it is a print only model.
 - ² Time between device power-on and when the start key is enabled. Quick start-up Mode ON.
 - ³ Time until key operation can be performed on the touch panel display.
 - ⁴ Only PDF print from websites is supported.
 - ⁵ 0.8W sleep mode is not available in all circumstances due to certain settings.
 - ⁶ Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh). The test methodology is defined by Energy Star (<http://www.eu-energystar.org>).
 - ⁷ Declared noise emission in accordance with ECMA-74.
 - ⁸ Common Criteria Certification (DIN ISO 15408) - Testing is scheduled to be finalised by the end of April 2018.
 - ⁹ Linux Drivers will be available from the beginning of March 2018.

Software & Solutions



Certifications and compatibility



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2018



Hay's Lane
London
SE1 2HB
Tel: 020 7536 2300
Email:
sales@ommdigital.co.uk
www.ommdigital.co.uk